



SAP60C-10 PAVER



SAP60C-10
PAVER

Official Website:
www.sanyglobal.com

Contact: _____
E-mail: _____



Technical specifications

| Model | SAP60C-10 |
|-----------------------------------|-----------------------------------|
| Paving capacity (t/h) | 450 |
| Paving width (m) | Hydraulic: 6 (2~3.7+0.75×2+0.4×2) |
| Basic width (m) | Hydraulic: 2~3.7 |
| Max. paving thickness (cm) | 25 |
| Working speed (m/min) | 1~20 |
| Travel speed (km/h) | 0~3 |
| Transport size (mm) | Hydraulic: 6210×2180×3080 |
| Engine brand | DONGFENG CUMMINS |
| Engine model | QSB4.5-C160 |
| Rated power of engine (kW) | 119 |
| Emission standard | CHINA III |
| Voltage of electric system (V) | 24 |
| Gradeability | ≥ 20% |
| Hopper capacity (m ³) | 6 |
| Frequency of oscillation (Hz) | 0~40 |
| Heating mode | Electric heated |
| Camber adjustment range | -1~3 |
| Tamps | 1 |
| Amplitude of tamp (mm) | 4 |
| Frequency of tamp (Hz) | 0~25 |
| Machine weight (kg) | 15800 |

技术参数

| 型号 | SAP60C-10 |
|------------------------|-----------------------------|
| 最大理论生产能力 (t/h) | 450 |
| 最大摊铺宽度 (m) | 伸缩板: 6 (2~3.7+0.75×2+0.4×2) |
| 基本宽度 (m) | 伸缩板: 2~3.7 |
| 最大摊铺厚度 (cm) | 25 |
| 工作速度 (m/min) | 1~20 |
| 行驶速度 (km/h) | 0~3 |
| 运输尺寸 (mm) | 伸缩板: 6210×2180×3080 |
| 发动机品牌 | 东风康明斯 |
| 发动机型号 | QSB4.5-C160 |
| 额定功率 (kW) | 119 |
| 排放标准 | 国III |
| 电控系统电压 (V) | 24 |
| 最大爬坡能力 | ≥ 20% |
| 料斗容量 (m ³) | 6 |
| 振动频率 (Hz) | 0~40 |
| 加热方式 | 电加热 |
| 拱度调节范围 | -1~3 |
| 振捣数量 | 1 |
| 振捣振幅 (mm) | 4 |
| 振捣频率 (Hz) | 0~25 |
| 整机重量 (kg) | 15800 |